

## 1. Identification

<b>GHS product identifier</b>	<b>LUMIFLON LF910LM</b>
<b>SDS number</b>	AGC-J-2990
<b>Version No.</b>	01
<b>Issue date</b>	17-December-2020
<b>CAS #</b>	Mixture
<b>Recommended use</b>	Raw material for industry
<b>Recommended Restrictions</b>	Not available.
<b>Manufacturer</b>	
<b>Company name</b>	AGC Inc. Chemicals Company Coating Business Group
<b>Address</b>	1-5-1, Marunouchi, Chiyoda-ku, Tokyo 100-8405, Japan
<b>Phone number</b>	+81-3-3218-5040
<b>Fax</b>	+81-3-3218-7843
<b>Emergency telephone number</b>	Verisk 3E (Access Code 335170)
	Europe: +0-800-680-0425
	Asia Pacific: +1-760-476-3960,+66-21056177, +81-368908677
	Middle East & Africa: +1-760-476-3959
	US, Canada,Mexico: +1-866-519-4752
	Other countries: +1-760-476-3971

## 2. Hazards identification

### GHS classification

<b>Physical hazards</b>	Flammable liquids	Category 3
	Pyrophoric liquids	Not classified
<b>Health hazards</b>	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Carcinogenicity	Category 2
	Reproductive toxicity	Category 1B
	Specific target organ toxicity following single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity following single exposure	Category 3 narcotic effects
	Specific target organ toxicity following repeated exposure	Category 1 (nervous system, respiratory organ)
	Aspiration hazard	Not classified
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
	Hazardous to the ozone layer	Classification not possible

### GHS label elements

**Signal word** Danger



### Hazard statement

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H370	Causes damage to organs (central nervous system, kidney, liver, respiratory organ).
H372	Causes damage to organs (nervous system, respiratory organ) through prolonged or repeated exposure.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

## Precautionary statement

### Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe mist/vapours.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P311	IF exposed or concerned: Call a POISON CENTRE/doctor.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use appropriate media to extinguish.
P391	Collect spillage.

### Storage

P235	Keep cool.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

### Other hazards which do not result in classification

None known.

### Supplemental information

None.

## 3. Composition/information on ingredients

Components	CAS #	Percent
Fluoro resin	Trade Secret	66
Xylene	1330-20-7	18
Ethylbenzene	100-41-4	16

## 4. First aid measures

### First aid procedures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. Oxygen or artificial respiration if needed. Get medical attention immediately.
<b>Skin</b>	Wipe up with absorbent material (e.g. cloth, fleece). Wash off with soap and plenty of water. Do not use solvents and thinner for wipe up. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
<b>Eye</b>	Get medical attention immediately. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

<b>Ingestion</b>	Rinse mouth. Call a physician or poison control centre immediately. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms and effects, both acute and delayed</b>	Not available.
<b>Notes to physician</b>	Provide general supportive measures and treat symptomatically.
<b>General advice</b>	Take off all contaminated clothing immediately.  If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
<b>5. Fire-fighting measures</b>	
<b>Suitable extinguishing media</b>	Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back.  During fire, gases hazardous to health may be formed. In the event of a fire, toxic gases such as hydrogen chloride, hydrogen fluoride, halocarbonyl, and carbon monoxide may be generated.
<b>Protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In case of fire and/or explosion do not breathe fumes.
<b>Protection of fire-fighters</b>	Move containers from fire area if you can do so without risk. Fight fire from upwind area.
<b>General fire hazards</b>	Flammable liquid and vapour.
<b>Specific methods</b>	Remove flammable materials from the environment Use designated extinguishing media.
<b>6. Accidental release measures</b>	
<b>Personal precautions</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up.  Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.  Prepare a suitable fire extinguisher in case of ignition.
<b>Environmental precautions</b>	Do not discharge to rivers. Be careful not to cause environmental impact Collect and dispose of spillage as indicated in section 13 of the SDS.
<b>Methods for containment</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas.
<b>Methods for cleaning up</b>	Ventilate the contaminated area. Wear appropriate protective equipment and clothing during clean-up. This product is miscible in water. Prevent product from entering drains. Do not allow material to contaminate ground water system.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use.; For waste disposal, see section 13 of the SDS.

## 7. Handling and storage

### Handling

All equipment used when handling the product must be grounded.

Take precautionary measures against static discharges.  
Explosion-proof general and local exhaust ventilation.

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight.

Use non-sparking tools and explosion-proof equipment.  
Do not breathe mist/vapours.  
Avoid contact with eyes, skin, and clothing.  
Avoid prolonged exposure.  
When using, do not eat, drink or smoke.  
Pregnant or breastfeeding women must not handle this product.  
Should be handled in closed systems, if possible.  
Use only outdoors or in a well-ventilated area.  
Wear appropriate personal protective equipment.  
Wash hands thoroughly after handling.  
Avoid release to the environment.  
Observe good industrial hygiene practices.

### Storage

Store locked up.  
Keep away from heat, sparks and open flame.  
Prevent electrostatic charge build-up by using common bonding and grounding techniques.

Store in a cool, dry place out of direct sunlight.  
Store in tightly closed container.  
Store in a well-ventilated place.  
Keep in an area equipped with sprinklers.  
Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls / personal protection

### Control parameters

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

### Biological limit values

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

### Recommended monitoring procedures

Follow standard monitoring procedures.

### Engineering controls

Provide eyewash station and safety shower. In case of indoor work, use auto application equipment or local ventilation equipment to prevent a worker from directly being exposed. When handling indoors, seal the source, or install a local exhaust system. In case of working at closed place such as inner of tank, install ventilation equipment to ventilate up to the bottom of closed place.  
Do not place high temperature or ignition source close to working place with this product.  
Earth equipments for transportation, collection and stirring of this product.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Skin protection

Wear appropriate chemical resistant clothing.  
Use of an impervious apron is recommended.

<b>Respiratory protection</b>	Chemical respirator with organic vapour cartridge.
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Liquid.
<b>Colour</b>	pale yellow colorless
<b>Form</b>	Not available.
<b>Odour</b>	Not available.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Boiling point</b>	138 - 144 °C (280.4 - 291.2 °F)
<b>Flash point</b>	26.2 °C (79.2 °F) Tag closed cup
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Flammability limits in air, lower, % by volume</b>	1 %
<b>Flammability limits in air, upper, % by volume</b>	7.6 %
<b>Vapour pressure</b>	0.6 - 0.9 kPa (20°C)
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	hardly soluble < 0.6 % (Solubility of fluororesin in water)
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	464 - 564 °C (867.2 - 1047.2 °F)
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Density</b>	1.12 g/cm <sup>3</sup>

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	Strong acids, strong oxidizing substances, and halogens can cause fires and explosions. Vapours may form explosive mixture with air. May ignite on contact with high surface temperature, sparks or open flame.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point.
<b>Incompatible materials</b>	Strong acids. Strong oxidising agents. Halogens.
<b>Hazardous decomposition products</b>	Hydrogen chloride. Hydrogen fluoride. carbon monoxide and carbon dioxide.

## 11. Toxicological information

### Toxicological data

Components	Species	Test Results
Ethylbenzene (CAS 100-41-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	15400 mg/kg
<b>Inhalation</b>		
LC50	Rat	4000 ppm, 4 hr
<b>Oral</b>		
LD50	Rat	3500 mg/kg

Components	Species	Test Results
Xylene (CAS 1330-20-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 4350 mg/kg
<b>Inhalation</b>		
LC50	Rat	29.08 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	3500 mg/kg
<b>Routes of exposure</b>	Inhalation. Skin contact. Eye contact.	
<b>Toxicological information</b>	Occupational exposure to the substance or mixture may cause adverse effects.	
<b>Acute toxicity</b>		
<b>Skin corrosion/irritation</b>	Causes skin irritation (Xylene)	
<b>Serious eye damage/eye irritation</b>	Causes serious eyes irritation(Xylene)	
<b>Irritation Corrosion - Eye</b>		
Xylene		Category2
Ethylbenzene		Category2A
<b>Respiratory sensitiser</b>	Not available.	
<b>Skin sensitisation</b>	Not available.	
<b>Mutagenicity</b>		
<b>Germ cell mutagenicity: Ames test</b>		
LUMIFLON LF910LM		OECD 471 Result: Negative
Ethylbenzene		Result: Negative
Xylene		Result: Negative
<b>Germ cell mutagenicity: Chromosome aberration</b>		
Ethylbenzene		Result: Negative
Xylene		Result: Negative
<b>Germ Cell Mutagenicity: In Vitro Mammalian Cell Gene Mutation Tests</b>		
Ethylbenzene		Result: There are both negative and positive reports.
Xylene		Result: There are both negative and positive reports.
<b>Germ Cell Mutagenicity: Micronucleus</b>		
Ethylbenzene		Result: Negative
Xylene		Result: Negative
<b>Carcinogenicity</b>		
Ethylbenzene		Category2
<b>ACGIH Carcinogens</b>		
Ethylbenzene (CAS 100-41-4)		A3 Confirmed animal carcinogen with unknown relevance to humans.
Xylene (CAS 1330-20-7)		A4 Not classifiable as a human carcinogen.
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
Ethylbenzene (CAS 100-41-4)		2B Possibly carcinogenic to humans.
Xylene (CAS 1330-20-7)		3 Not classifiable as to carcinogenicity to humans.
<b>Reproductive toxicity</b>	Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.	
<b>Reproductivity</b>		
Ethylbenzene		Category1B
Xylene		Category1B
<b>Specific target organ toxicity - single exposure</b>	May cause respiratory irritation. May cause drowsiness and dizziness.	
Xylene		Cat.1(Central nervous system,Respiratory,Liver,Kidney), Cat.3( Narcrotic
Ethylbenzene		Cat.3 (Respiratory irritation, Narcotic effect)
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs (nervous system, respiratory organ) through prolonged or repeated exposure.	
Xylene		Cat.1 ( Nervous system,Respiratory organs )
Ethylbenzene		Category2(Hearing organs)
<b>Aspiration hazard</b>	Not applicable.	

**Aspiration hazard**

Xylene

Category1

**Chronic effects**

Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

**Teratogenicity**

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

**Symptoms**

May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioural changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Oedema. Jaundice.

**12. Ecological information****Ecotoxicological data**

Product	Species	Test Results
---------	---------	--------------

LUMIFLON LF910LM

**Aquatic**

Crustacea

LC50

Brown shrimp (*Penaeus aztecus*)

0.4 mg/l, 96 Hours (ethylbenzene)

Fish

LC50

Rainbow trout

3.3 mg/l, 96 Hours (xylene)

**Components****Species****Test Results**

Ethylbenzene (CAS 100-41-4)

**Aquatic***Acute*

Crustacea

EC50

Water flea (*Daphnia magna*)

1.37 - 4.4 mg/l, 48 hours

Fish

LC50

Atlantic silverside (*Menidia menidia*)

4.4 - 5.7 mg/l, 96 hours

Xylene (CAS 1330-20-7)

**Aquatic***Acute*

Fish

LC50

Rainbow trout, donaldson trout  
(*Oncorhynchus mykiss*)

3.3 mg/l, 96 hours

**Ecotoxicity**

Toxic to aquatic life with long lasting effects. In case of leakage, disposal etc., there is a risk of influencing the environment, so handle with care. Especially when products and washing water. Take measures not to flow directly to the ground, river or drainage.

**Environmental effects**

Toxic to aquatic life with long lasting effects. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

**Persistence and degradability**

Easily biodegraded. (Xylene)

**Bioaccumulation****Bioaccumulative potential****Octanol/water partition coefficient log Kow**

Ethylbenzene

3.15

**Aquatic toxicity**

Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

**Mobility**

Not available.

**Other adverse effects**

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations****Disposal methods**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Do not allow this material to drain into sewers/water supplies.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Waste generated by wastewater treatment, incineration, etc. shall be processed or consigned according to Waste Management and Public Cleansing Act. and the related laws.

Do not flush wastewater cleaned in containers, equipment, etc. to the ground or drain.

Since waste generates hydrogen chloride and hydrogen fluoride when incinerated, it is incinerated in an incinerator equipped with neutralization facility and the incinerated residue is land filled in legally right place. Do not incinerate in the case of exceeding fluorine emission standards.

**Waste from residues / unused products**

Dispose of in accordance with local regulations.

Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

The remaining products (residual waste) should be discarded according to the law concerning waste disposal and cleaning and the prefectural / municipal regulations.

**Contaminated packaging**

Since emptied containers may retain product residue, follow label warnings even after container is emptied.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

**14. Transport information****ADR**

**UN number** 1866  
**UN proper shipping name** RESIN SOLUTION, flammable  
**Transport hazard class(es)**  
 Class 3  
 Subsidiary risk -  
 Label(s) 3  
 Hazard No. (ADR) 30  
 Tunnel restriction code D/E  
**Packing group** III  
**Environmental hazards** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**RID**

**UN number** 1866  
**UN proper shipping name** RESIN SOLUTION, flammable  
**Transport hazard class(es)**  
 Class 3  
 Subsidiary risk -  
 Label(s) 3  
**Packing group** III  
**Environmental hazards** No.  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**IATA**

**UN number** 1866  
**UN proper shipping name** Resin solution flammable  
**Transport hazard class(es)**  
 Class 3  
 Subsidiary risk -  
**Packing group** III  
**Environmental hazards** No.  
**ERG Code** 3L  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.  
**Other information**

**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

**IMDG**

**UN number** 1866  
**UN proper shipping name** RESIN SOLUTION flammable, MARINE POLLUTANT  
**Transport hazard class(es)**  
 Class 3  
 Subsidiary risk -  
**Packing group** III  
**Environmental hazards**  
 Marine pollutant Yes  
**EmS** F-E, S-E  
**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to IMO instruments** Not established.

**ADR; IATA; IMDG; RID**



## Marine pollutant



### General information

IMDG Regulated Marine Pollutant. In case of falling under the Fire Service Law, Occupational Safety and Health Law, Poisonous and Deleterious Substances Control Law, follow the transportation method prescribed by each applicable law.

To comply with the provisions of the ship safety law. Follow the aviation laws.

When transporting, keep the container at 40 ° C or below, taking care not to fall over, fall, or damage.

## 15. Regulatory information

### Regulatory information

Ensure this materials in compliance with federal requirements and ensure conformity to local regulation.

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information

### Disclaimer

AGC Inc. Chemicals Company Coating Business Group

SDS is a document for business operators. Not all materials and literature have been investigated, so there may be information leaks. In addition, the content will change due to the announcement of new knowledge and correction of the existing theory. When used for important decisions, it is recommended to examine the sources carefully and to confirm by examination. No guarantee is made for the data or evaluation described. In addition, the items described are intended for normal handling. Therefore, when handling specially, be sure to implement safety measures suitable for new applications and usages before handling. Attach this SDS when transferring this product.

This product is an industrial product, it is not the thing which developed / manufactured assuming the medical use.